SPECIFICATION

Product number: G286AY540-S01

Product type: Bus display





Checked by	Rechecked by	Approved by
Comments	Approved by	Company's seal
	Customer's Name:	

Please send the original back to us after you have approved and signed.

Modify History


Ver.	Page	Revised Descriptions	Date	Revision	Approal
REV.1.0	ALL	ТО	2025.05.16		

Product Paramenter:

	28.6"	Specifications	Units/N	Notes
Mod	del	1	umber	
	Dimension	788(L)*282(W)*71.8(H)	MM	
	Shell material	creamy-white	-	
	Gross Weight	7.7	Kg/gros s	
	Display Size	698.4(L)*196.43(V)	MM	
Screen Param-eters	Display- resolution	1920*540	Pixel	
	Brightness	500	Cd/m²	
	Contrast ratio	1200: 1	-	
	Display scale	16:4.5	-	
	Viewing angle	89/89/89	-	
	Pixel pitch	0.36375*0.36375	MM	
	Display color	16.7	М	
Electrical	Maximum power	≤45	W	
	Standby power	≤1	W	
	Supply Voltage	12	V	
	Horn	5W/8 Ω*2	-	
	Operating temperature	0-50	$^{\circ}$ C	
WorkStorage	Working- humidity	10%~80%	%hr	
	Storage temperature	-20-50	$^{\circ}$ C	
	Storage Humidity	10%~80%	%hr	

Mod	28.6"	Specifications	Units/N umber	Notes
	СРИ	TA40i, quad-core, the highest main frequency is 1.2GHz		
	Operating System	Android 7.1		
	Memory Storage	EMMC is standard with 8G (16/32G optional)		
	built-inROM	2KB EEPROM		
	HDMI Out	1, supports 1080P output		
	HDMI import	/		
Fun	Support Video- Formats	Supports wmv, avi, flv, rm, rmvb, mpeg, ts, mp4, etc		
Functional configuration	Support Image- Formats	Supports BMP, JPEG, PNG, GIF		
	Audio Input/Output	Supports left and right channel output, with built-in dual 4R/20W and 8R/10W power amplifiers		
	Headphone Output	/		
	USB Interface	2 USB HOST, 3 USB ports		
	Serial Port	2 serial TTL sockets, 2 serial RS232 sockets		
	Network Support	4G, Ethernet, support WiFi/ Bluetooth 4.0, wireless peripheral expansion		
	Memory Card	Supports SD cards		
	RTC	Support multi-time timing on and off		
	System Upgrade	Support local SD, USB upgrade		

Product Rendering:



Product Dimension Drawing:

