
SPECIFICATION

Product number: G431AY360-S01

Product type: Metro display



Checked by	Rechecked by	Approved by
Comments	Approved by	Company's seal
	Customer's Name:	

Please send the original back to us after you have approved and signed.

Modify History

Ver.	Page	Revised Descriptions	Date	Revision	Approal
REV.1.0	ALL	ТО	2025.05.16		


Product Paramenter:

Mod	43.1"	Specifications	Units/N umber	Notes
	Dimension	1122.5(H)*239(V)*27(W)	MM	
	Shell material	Black fine sand texture	-	
	Gross Weight	/	Kg/gros s	
	Display Size	1073.78(H)*201.1(V)	MM	
Screen Param-eters	Display- resolution	1920x360	Pixel	
	Brightness	700	Cd/m²	
	Contrast ratio	3000:1	-	
	Display scale	16:3	-	
ters	Viewing angle	178/178/178	-	
	Pixel pitch	0.55926*0.55926	MM	
	Display color	16.7	М	
	Maximum power	≤80	W	
Elec	Standby power	≤1	W	
ectrical	Supply Voltage	12	V	
	Horn	/	-	
	Operating temperature	0-50	$^{\circ}$	
WorkStorage	Working- humidity	10%~80%	%hr	
	Storage temperature	-20-50	$^{\circ}$ C	
	Storage Humidity	10%~80%	%hr	
	Power interface	DC 110V		

Copyright GOMANY belongs to GOMANY. The contents of this document are commercial secrets. No organization or individual may copy or disseminate in any form without permission.

Mod	43.1" lel	Specifications	Units/N umber	Notes
Functional configuration	СРИ	Т3		
	Operating System Android 7.1/linux3.10.0			
	Memory Storage	EMMC standard with 8G, (16 / 32G optional)		
	built-inROM 2GBB EEPROM			
	HDMI Out	/		
	HDMI import	/		
	Support Video- Formats	Support for wmv, avi, flv, rm, rmvb, mpeg, ts, mp4, etc		
	Support Image- Formats	Support for BMP, JPEG, PNG, and GIF		
	Audio Input/Output	/		
	Headphone Output	/		
	USB Interface	1. USB2.0 OTG/USB HOST		
	Serial Port	/		
	Network Support	MII, RMII, and RGMII supporting 10 / 100 / 1000Mbps		
	Memory Card	Support for the SD card		
	RTC	support		
	System Upgrade	Support for USB /network/SD block		

Product Rendering:



Product Dimension Drawing:

