SPECIFICATION

Product number: G370AV540-S01

Product type: Double noodle shaped display





Checked by	Rechecked by	Approved by
Comments	Approved by	Company's sea
	Customer's Name:	

Please send the original back to us after you have approved and signed.

Modify History

Ver.	Page	Revised Descriptions	Date	Revision	Approal
REV.1.0	ALL	ТО	2025.05.16		

Product Paramenter:

	37"		Units/N	
Model		Specifications	umber	Notes
	Dimension	905(H)×270 (V)×55W)	MM	
	Shell material	white	-	
	Gross Weight	/	Kg/gros s	
	Display Size	878.11(H)×242.67(V)	MM	
	Display- resolution	1920*540	Pixel	
Sc	Brightness	400	Cd/m²	
Screen Param-eters	Contrast ratio	5000: 1	-	
aram-e	Display scale	16:4.4	-	
eters	Viewing angle	89/89/89	-	
	Pixel pitch	0.45735×0.4494	MM	
	Display color	16.7	М	
	Maximum power	≤120	W	
Elec	Standby power	≤1	W	
ectrical	Supply Voltage	12V	V	
	Horn	8 Ω3W*2	-	
WorkStorage	Operating temperature	0-50	$^{\circ}$	
	Working- humidity	10%~80%	%hr	
	Storage temperature	-20-50	$^{\circ}$ C	
Ø	Storage Humidity	10%~80%	%hr	
	Power interface	AC 110-240V		

Copyright GOMANY belongs to GOMANY. The contents of this document are commercial secrets. No organization or individual may copy or disseminate in any form without permission.

Mod	37" lel	Specifications	Units/N umber	Notes
	СРИ	The quad-core 64-bit Cortex-A55 has a maximum frequency of 2.0GHz		
	Operating System	Android 11.0		
	Memory Storage	Standard 8G		
	built-inROM	/		
	HDMI Out	HDMI2.0 supports up to 4K@60HZ output		
	HDMI import	/		
Fund	Support Video- Formats	Support wmv, avi, flv, rm, rmvb, mpeg, ts, mp4, etc		
Functional configuration	Support Image- Formats	Supports BMP, JPEG, PNG, GIF		
onfigura	Audio Input/Output	Supports a speaker interface, up to one 8Ω 5W Dual-channel speaker output		
tion	Headphone Output	Standard 3.5mm, 4 section earphone headset base, CTIA (US standard) standard		
	USB Interface	1 *USB3.0 host,1*USB3.0_OTG		
	Serial Port	4 TTL serial ports (1 optional TTL/RS232/RS485,3 optional TTL/RS232), one of which is a debugging serial port		
	Network Support	Supports 1000M/100M adaptive Ethernet and WIFI-2.4G BT-4.1 4G module interface		
	Memory Card	/		
	RTC	/		
	System Upgrade	Supports local USB upgrades		

Product Rendering:









Product Dimension Drawing:

