SPECIFICATION

Product number: G700AWE40-D01

Product type: Vertical full screen display





Checked by	Rechecked by	Approved by
Comments	Approved by	Company's seal
	Customer's Name:	

Please send the original back to us after you have approved and signed.

Modify History

Ver.	Page	Revised Descriptions	Date	Revision	Approal
REV.1.0	ALL	ТО	2025.05.16		

Product Paramenter:

Mod	70"	Specifications	Units/N umber	Notes
IVIO	Dimension	1780.6 (H) x 680.6 (V) x 74 (W) (including base)	MM	
	Shell material	Black fine sand pattern	-	
	Gross Weight	/	Kg/gros	
Screen Param-eters	Display Size	1649.66(H)× 618.62(V)	MM	
	Display- resolution	3840*1440	Pixel	
	Brightness	350	Cd/m²	
	Contrast ratio	1200: 1	-	
	Display scale	16:6	-	
	Viewing angle	89/89/89	-	
	Pixel pitch	0.4296*0.4296	MM	
	Display color	1.07	В	
Electrical	Maximum power	≤70	W	
	Standby power	≤1	W	
	Supply Voltage	12	V	
	Horn	5W/8 Ω*2	-	
WorkStorage	Operating temperature	0-50	$^{\circ}$ C	
	Working- humidity	10%~80%	%hr	
	Storage temperature	-20-50	${\mathbb C}$	
	Storage Humidity	10%~80%	%hr	
	Power interface	AC 110-240V		

Copyright GOMANY belongs to GOMANY. The contents of this document are commercial secrets. No organization or individual may copy or disseminate in any form without permission.

Mod	70"	Specifications	Units/N umber	Notes
Functional configuration	СРИ	The T972 quad-core A55 has a maximum frequency of 1.9GHz,		
	Operating System	Android 9.0		
	Memory Storage	Standard 2GB (1G/4G optional)Standard 16GB (16/32/64GB optional)		
	built-inROM	/		
	HDMI Out	/		
	HDMI import	1, supports HDMI 2.1 4kx2k@60Hz input		
	Support Video- Formats	Supports H.265, H.264, VP8, MAV, WMV, AVS, H.263, MPEG4 and other video formats		
	Support Image- Formats	Supports JPG, BMP, PNG and other image formats		
	Audio Input/Output	Supports left and right channel output, built-in dual $8\Omega/9.5W$ power amplifier		
	Headphone Output	Supports 1 headphone jack		
	USB Interface	1 USB OTG A port, 1 USB2.0 A port		
	Serial Port	1 The serial port is available		
	Network Support	WIFI, Ethernet		
	Memory Card	/		
	RTC	Support multi-time timing on and off		
	System Upgrade	Support local TF, USB upgrade and remote upgrade		

Product Rendering:















Product Dimension Drawing:

