
SPECIFICATION

Product number: G298BYK00-D01

Product type: Square screen display





Checked by	Rechecked by	Approved by
Comments	Approved by	Company's seal

Please send the original back to us after you have approved and signed.

Modify History

Ver.	Page	Revised Descriptions	Date	Revision	Approal
REV.1.0	ALL	ТО	2025.05.28		

Product Paramenter:

Mod	29.8" del	Specifications	Units/N umber	Notes
	Dimension	571(L)*571(H)x50(W)	MM	
	Shell material	Black fine sand texture	-	
	Gross Weight	/	Kg/gros s	
Screen Param-eters	Display Size	542.2(L)x 542.2(H)	MM	
	Display- resolution	1900*1900	Pixel	
	Brightness	400	Cd/m²	
	Contrast ratio	4000:1	-	
	Display scale	1:1	-	
	Viewing angle	89/89/89	-	
	Pixel pitch	0.285375*0.285375	MM	
	Display color	1.07	В	
Electrical	Maximum power	≤85	W	
	Standby power	≤1	W	
	Supply Voltage	12V	V	
	Horn	3W/8 Ω*2	-	
WorkStorage	Operating temperature	0-50	$^{\circ}$	
	Working- humidity	10%~80%	%hr	
	Storage temperature	-20-50	$^{\circ}$	
	Storage Humidity	10%~80%	%hr	
	Power interface	AC 110-240V		

Copyright GOMANY belongs to GOMANY. The contents of this document are commercial secrets. No organization or individual may copy or disseminate in any form without permission.

Mod	29.8" el	Specifications	Units/N umber	Notes
	СРИ	RK3288, quad-core, 1.8GHz, Android 5.1.1		
	Operating System	Android 5.1.1		
	Memory Storage	Standard 2G (4G optional) / Standard 8G (16/32/64G optional)		
	built-inROM	/		
	HDMI Out	1, supports 1080P@120Hz, 4kx2k@60Hz output		
	HDMI import	/		
Fun	Support Video- Formats	Supports wmv, avi, flv, rm, rmvb, mpeg, ts		
Functional configuration	Support Image- Formats	Supports BMP, JPEG, PNG, GIF		
onfigura	Audio Input/Output	Supports left and right channel output, with built-in dual 4R/20W and 8R/10W power amplifiers		
tion	Headphone Output	Supports the insertion of one or two earphones		
	USB Interface	2 USB HOST		
	Serial Port	4 serial port sockets (2 TTL +2232), of which 1 is a Bluetooth multiplexed serial port		
	Network Support	Ethernet WIFI		
	Memory Card	Supports SD cards		
	RTC	Supports		
	System Upgrade	Supports local SD USB upgrades		

Product Rendering:



Product Dimension Drawing:

